



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® FAST 'N FINAL® LIGHTWEIGHT SPACKLING

### PRODUCT DESCRIPTION

**DAP® FAST 'N FINAL® LIGHTWEIGHT SPACKLING** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint in minutes. It is easy to apply with one strike. Won't sink, shrink or crack. Ideal for repairing holes, cracks and dents in drywall, plaster, wood and stucco. Interior/exterior use.



PACKAGING	COLOR	UPC
83 mL (2.8 fl oz) Tube	Off White	7079812317

### KEY FEATURES & BENEFITS

- Patch & prime in one step
- Fast Drying – Paint ready in 30 minutes
- No sanding
- Won't sink, shrink or crack
- Low odor
- Interior/exterior use

### SUGGESTED USES

**IDEAL FOR FILLING HOLES, CRACKS, CREVICES, DENTS AND DEFECTS ON:**

- Drywall
- Wood
- Plaster
- Stucco



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## FOR BEST RESULTS

- Apply in temperatures above 4°C
- Do not apply if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with a coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick.
- Store away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of foreign material.

### Product Application

1. Remove the top, grip tube bottom and twist up a very small amount of filler.
2. Either apply directly to the surface or using the built-in spackling knife, scrape off spackling from the top of the tube and apply to wall.
3. Press spackling into hole or crack.
4. Draw blade of spackling knife firmly across the surface to remove excess material in one strike.
5. One application is usually sufficient for small repairs. For repairs deeper than 3 mm, apply two or more layers allowing spackling to dry between applications.
6. May be painted within minutes with a latex paint. Follow paint manufacturer's instructions for application.
7. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).
8. Clean tools immediately with water.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	Thick paste
Vehicle	Latex polymer
Filler	Inert Filler
Volatile	Water
Volume Solids	75% by volume
Odor	Very mild



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Clean Up	Water
Freeze Thaw Stability (ASTM C1183)	Passes 5 Cycles
Shelf Life	12 months
Application Temperature Range	Above 4°C
Service Temperature Range	-29°C to 65°C
Paint Ready Time	30 minutes w/ latex or oil-based paints

## CLEAN UP & STORAGE

Wash tools immediately after use with water. Excess dried material must be scraped or sanded away. Clean hands with warm water and soap. Be sure container lid/cap is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information.

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM AUSTRALIA & NEW ZEALAND PTY LTD  
Level 2, 307 Ferntree Gully Road  
Mount Waverley, Victoria 3149 Australia  
PH: 1 300 784 476  
Email: [technical@rustoleum.com.au](mailto:technical@rustoleum.com.au)  
[www.rustoleum.com.au](http://www.rustoleum.com.au)

4/20/2021