



# TECHNICAL DATA SHEET

## DAP® FAST DRY Premium Lightweight Large Repair Wall Filler

### PRODUCT DESCRIPTION

DAP® FAST DRY is an advanced, ultra tough, lightweight wall filler uniquely formulated to provide superior strength and fast drying capabilities, allowing the repair to be painted in as little as 15 minutes. Its ready-to-use, smooth formula spreads easily and won't sink, sag, shrink or crack, filling even the largest of plasterboard repairs. It has high strength and impact resistance for an ultra-tough, long-lasting repair. No spot priming required and won't flash or discolor paint. Interior/exterior use.



PACKAGING	COLOR	UPC
Pint 473 mL	Off White	7079818440
Quart 846 mL	Off White	7079818441

### KEY FEATURES & BENEFITS

- Ultra tough, ultra fast
- Ideal for large repairs; fills gaps up to 50 mm deep
- Easy handling, lightweight formula
- Fast 15 minute dry time. 8X faster finish\*
- Strong impact resistance for a durable, long-lasting repair. 3X\*\* stronger
- Can be nailed or screwed
- One strike – Won't sink, sag, shrink or crack
- Easy to sand & smooth
- No spot priming required
- Won't flash or discolor paint
- Easy water clean-up & low odor
- 2X\*\*\* longer lasting – won't dry out
- Ready to use
- Interior/exterior use

*\*Than traditional heavyweight spackling \*\* Than other spackling compounds \*\*\* Than competitive product.*



# TECHNICAL DATA SHEET

## SUGGESTED USES

Ideal for filling large and small holes, cracks, dents and defects in wood, plaster, plasterboard, stone, brick, concrete, primed nail holes.

## PREPARATION

Surface must be clean (free from dirt, dust, grease, debris), dry & structurally sound. De-gloss surface if necessary. Do not apply when temperatures are below 4°C. Do not apply outside if rain is expected within 24 hours. For exterior applications, always overcoat with a high quality exterior grade paint prior to water exposure. Do not use as a skim coat, on floors, as a sealant or as a joint filler over cracks and joints where expansion and contraction may occur.

## APPLICATION

1. If filler seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.
2. Apply with a clean filling knife, pressing filler firmly into hole.
3. Smooth over filler with a dry filling knife prior to product drying.
4. One application is usually sufficient. Repairs 2.5 cm wide x 3 mm in depth or smaller may be painted in as little as 15 minutes (depending on temperature, humidity & depth of fill). Larger and deeper repairs may require longer drying time, up to 60 minutes.
5. If sanding is necessary, additional dry time may be needed. Use medium-grit sandpaper and finish with fine-grit for a smooth finish. Avoid the inhalation of dust and wear a suitable face mask when sanding.
6. Paintable with latex or oil-based paints. Ensure wall filler is thoroughly dry if painting with oil-based paint.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste (contents may appear dry upon opening)
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler



# TECHNICAL DATA SHEET

Odor	Mild
Density	0.605 g/cm <sup>3</sup>
Solids	63%
Application Temperature	Do not apply when temperatures are below 4°C
Service Temperature	-17°C to 65°C
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at -17°C
Dry Time	15 min time to paint (3mm depth, depending on temperature, humidity and depth of fill)

## CLEAN UP & STORAGE

Clean tools immediately with a cloth and water before product dries. Dried material must be cut or scraped away. Ensure lid is closed and tightly closed to prevent product from drying out. Store container in a cool, dry place away from extreme heat or cold. Protect from freezing.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information.

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages. The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM AUSTRALIA & NEW ZEALAND PTY LTD  
Level 2, 307 Ferntree Gully Road  
Mount Waverley, Victoria 3149 Australia  
PH: 1 300 784 476  
Email: [technical@rustoleum.com.au](mailto:technical@rustoleum.com.au); [www.rustoleum.com.au](http://www.rustoleum.com.au)



# TECHNICAL DATA SHEET