



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® ALEX PLUS® PREMIUM SPACKLING

PRODUCT DESCRIPTION

DAP® ALEX PLUS® PREMIUM SPACKLING is a professional-grade, heavyweight filler that provides an ultra-smooth surface and superior paintability for a repair that disappears when painted. Its de-aired, smooth and creamy formula spreads easily for fine surface finishing and fast, long-lasting repairs that won't crack, crumble or flake. It sands effortlessly, doesn't require spot priming and won't flash paint. It provides high strength and durability with strong impact resistance and the ability to be nailed or screwed without cracking or lifting. Paintable in 1- 2 hours. Alex Plus is ideal for repairing holes, cracks and dents up to 10 mm deep in plasterboard, plaster, wood, brick and more. Easy water clean-up and low odor. Interior/exterior use.



PACKAGING	COLOR	UPC
207 mL (7 oz) Tube	White	7079818744
473 mL (16 oz) Tub	White	7079818745
946 mL (32 oz) Tub	White	7079819746
3.7 L (128 oz) Tub	White	7079818747

KEY FEATURES & BENEFITS

- Professional strength repairs & fine surface finishing
- One strike application
- Non-sagging – will not crack, crumble or flake
- Sands effortlessly
- Superior paintability – won't flash or discolor paint
- Exceptional durability: high impact resistance; can be nailed or screwed
- Paintable in 1-2 hours
- Low odor & easy water clean-up
- Interior/exterior use



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

IDEAL FOR FILLING HOLES, CRACKS, CREVICES, DENTS AND DEFECTS ON:

- Drywall / Plasterboard
- Wood
- Plaster
- Stone
- Brick
- Metal Doors & Trim

FOR BEST RESULTS

- Apply in temperatures above 10°C
- Do not apply if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with a coating of quality exterior-grade paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- Store away from extreme heat or cold.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of dirt, debris and foreign material.

Product Application

1. For tubs, pry off lid. Mix if necessary. If using the squeeze tube, knead tube, cut nozzle & squeeze directly onto filling knife.
2. Using a clean filling knife, firmly press filler into hole or crack.
3. Draw blade firmly across the surface to remove excess material in one strike. Overfill slightly to allow for minimal shrinkage.
4. For a smoother finish, dip putty knife into water and pull from center of hole outwards (not from top to bottom or side to side).
5. For repairs deeper than 3 mm, apply two or more layers allowing spackling to dry between applications.
6. Allow to dry 1-2 hours (depending on temperature, relative humidity and depth of fill) and then sand and paint. Ensure that the filler is thoroughly dry before sanding or applying an oil-based paint. Spackling may be painted immediately upon drying with a quality latex paint.
7. Clean tools immediately with water before product dries & tightly reseal container and store away from extreme heat or cold.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	Thick paste
Vehicle	Latex polymer
Filler	Inert Filler
Volatile	Water
Volume Solids	76%
Odor	Very mild
Clean Up	Water
Freeze Thaw Stability (ASTM C1183)	Passes 5 Cycles
Shelf Life	12 months
Application Temperature Range	Above 10°C
Service Temperature Range	-17°C to 18°C
Paint Ready Time	1-2 hours depending on temperature, humidity and depth of fill

CLEAN UP & STORAGE

Wash tools immediately after use with water. Excess dried material must be scraped or sanded away. Clean hands with warm water and soap. Be sure container lid/cap is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM AUSTRALIA & NEW ZEALAND PTY LTD
Level 2, 307 Ferntree Gully Road
Mount Waverley, Victoria 3149 Australia
PH: 1 300 784 476
Email: technical@rustoleum.au
www.rustoleum.com.au

11/15/2021