



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® FAST 'N FINAL® LIGHTWEIGHT SPACKLING

PRODUCT DESCRIPTION

DAP® FAST 'N FINAL® LIGHTWEIGHT SPACKLING is a fast drying, easy-handling multi-purpose filler that lets you patch and prime in one easy step for improved productivity. It dries fast with no need to sand or spot prime, letting you paint in as little as 30 minutes. It is easy to apply with one strike and won't sink, shrink or crack. It is ideal for repairing holes, cracks and dents up to 10 mm deep in plasterboard, plaster, wood, brick and more. Easy water clean-up and low odor. Interior/exterior use.



PACKAGING	COLOR	UPC
88.7 mL (3 oz) Tube	White	7079812321
473 mL (16 oz) Tub	White	7079812141
946 mL (32 oz) Tub	White	7079812142
3.7 L (128 oz) Tub	White	7079812143

KEY FEATURES & BENEFITS

- Fast drying – Paint ready in 30 minutes
- No sanding needed
- Patch & prime in one step
- One coat coverage: Won't sink, shrink or crack
- Low odor & easy water clean-up
- All-in-One Applicator squeeze tube
- Interior/exterior use



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

IDEAL FOR FILLING HOLES, CRACKS, CREVICES, DENTS AND DEFECTS ON:

- Drywall / Plasterboard
- Wood
- Plaster
- Stucco / Brick

FOR BEST RESULTS

- Apply in temperatures above 4°C
- Do not apply if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with a coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick.
- Store away from extreme heat or cold.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of dirt, debris and foreign material.

Product Application

Tubs:

- Pry off lid. For squeeze tube, remove the cap and peel off foil seal. Re-attach cap.
- Mix *gently* if necessary. Using a clean knife, firmly press filler into hole or crack.
- Draw blade of spackling knife firmly across the surface to remove excess material in one strike.

All-in-One Squeeze Tube:

- For initial use, unscrew knife cap and peel off foil seal.
 - Screw knife cap back onto tube and remove plug.
 - Apply by squeezing spackling directly through the nozzle of the knife onto the surface being repaired.
 - Use the built-in putty knife to strike smooth.
1. For a smoother finish, dip putty knife into water and pull from center of hole outwards (not from top to bottom or side to side).
 2. One application is usually sufficient for small repairs. For repairs deeper than 3 mm, apply two or more layers allowing spackling to dry between applications.
 3. No sanding required. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

4. May be painted in 30 minutes or less with a latex-based paint. Follow paint manufacturer's instructions for application.
5. Clean tools immediately with water before product dries & tightly reseal container and store away from extreme heat or cold.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	Thick paste
Vehicle	Latex polymer
Filler	Inert Filler
Volatile	Water
Volume Solids	75% by volume
Odor	Very mild
Clean Up	Water
Freeze Thaw Stability (ASTM C1183)	Passes 5 Cycles
Shelf Life	12 months
Application Temperature Range	Above 4°C
Service Temperature Range	-29°C to 65°C
Paint Ready Time	30 minutes w/ latex-based paints

CLEAN UP & STORAGE

Wash tools immediately after use with water. Excess dried material must be scraped or sanded away. Clean hands with warm water and soap. Be sure container lid/cap is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information.

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM AUSTRALIA & NEW ZEALAND PTY LTD
Level 2, 307 Ferntree Gully Road
Mount Waverley, Victoria 3149 Australia
PH: 1 300 784 476
Email: technical@rustoleum.au
www.rustoleum.com.au

11/15/2021